



# Technical Data Sheet

## Backlit15M

### 15 oz. Scrim Banner Matte

*Ideal for Eco-Solvent, Solvent and UV Cure Ink Jet Printers*

PROPERTIES	METRIC	METHOD	RESULTS
TOTAL WEIGHT	440g/m <sup>2</sup>		15 oz/yd <sup>2</sup>
THICKNESS	0.4 +/- 0.02mm		
BASE FABRIC	Polyester 300 x 500D, 18x12/inch		
TENSILE STRENGTH		ASTM D5035	202 x 169 lbs/2"
TEAR STRENGTH		ASTM D1004	31 x 29 lbs
ADHESION		ASTM D5035	11 x 5 lbs/inch
COLD CRACK	at -20° C		at -4° F
RECOMMENDED WIDTH			54", 72" & 126"
STANDARD ROLL LENGTH			55 yds
REMARKS		Warp / Weft	
NOTE:	All above information shall only be used as a guide; Buyers shall independently test and determine the products suitability. The mentioned data is an average of test results and should not be used for the purpose of lawsuit or warranty.		
Application/Features	<ul style="list-style-type: none"> <li>Specially designed for billboard applications</li> <li>Outdoor and/or indoor backlit graphics</li> <li>This material is fire retardant to NFPA 701.</li> </ul>		



[www.myoutre.com](http://www.myoutre.com)

#1 Network  
309 Professional Park Avenue  
Effingham, IL 62401  
Phone: 217-536-5737  
Fax: 217-536-5141

7/30/10