



Technical Data Sheet

Blockout18M

18 oz. Scrim Banner Matte

Ideal for Eco-Solvent, Solvent and UV Cure Ink Jet Printers

PROPERTIES	METRIC	METHOD	RESULTS
TOTAL WEIGHT	610g/m ²		18 oz/yd ²
THICKNESS	0.48 +/- 0.02mm		
BASE FABRIC	Polyester 1000 x 1000D, 9x9/inch		
TENSILE STRENGTH		ASTM D5035	325.2 x 396.4 lbs/2"
TEAR STRENGTH		ASTM D1004	43.4 x 46.6 lbs
ADHESION		ASTM D5035	11 x 5 lbs/inch
COLD CRACK	at -20° C		at -4° F
RECOMMENDED WIDTH			39", 54" & 126"
STANDARD ROLL LENGTH			35 & 55 yds
REMARKS		Warp / Weft	
NOTE:	All above information shall only be used as a guide; Buyers shall independently test and determine the products suitability. The mentioned data is an average of test results and should not be used for the purpose of lawsuit or warranty.		
Application/Features	<ul style="list-style-type: none"> Printable on both sides with different images Compatible with solvent-based inks This material is fire retardant to NFPA 701. 		



www.myoutre.com

#1 Network
309 Professional Park Avenue
Effingham, IL 62401
Phone: 217-536-5737
Fax: 217-536-5141

7/30/10