



Technical Data Sheet

Frontlit13G & Frontlit 13M

13 oz. Scrim Banner Gloss and Matte

Ideal for Eco-Solvent, Solvent and UV Cure Ink Jet Printers

PROPERTIES	METRIC	METHOD	RESULTS
TOTAL WEIGHT	450g/m ²		13 oz/yd ²
THICKNESS	0.40 +/- 0.02mm		
BASE FABRIC	Polyester 500 x 500D, 18x12/inch		
TENSILE STRENGTH		ASTM D5035	202 x 169 lbs/2"
TEAR STRENGTH		ASTM D1004	31 x 29 lbs
ADHESION		ASTM D5035	11 x 5 lbs/inch
COLD CRACK	at -20° C		at -4° F
RECOMMENDED WIDTH			30", 39", 50", 54", 63", 72", 126" & 197"
STANDARD ROLL LENGTH			35 & 55 yds
REMARKS		Warp / Weft	
NOTE:	All above information shall only be used as a guide; Buyers shall independently test and determine the products suitability. The mentioned data is an average of test results and should not be used for the purpose of lawsuit or warranty.		
Application/Features	<ul style="list-style-type: none"> • Matte / Gloss finish treatment available • Specially designed for billboard applications • Outdoor and/or indoor backlit graphics • Tear resistant, fade resistant and fire retardant to NFPA 701. 		



www.myourtre.com

#1 Network
309 Professional Park Avenue
Effingham, IL 62401
Phone: 217-536-5737
Fax: 217-536-5141

7/30/10